

# Baths

## Open Heating Bath Circulators with stainless steel bath tank

### The 'Economy' Series

-35 °C to +150 °C

For routine laboratory applications



### The 'Top Tech' Series

-88 °C to +200 °C

These units are designed for more demanding applications and provide an improved operating comfort with menu functions, warning and safety installations



### The 'High Tech' Series

-95 °C to +300 °C

Top-of-the-line models: even EASIER to use and upgradable with HSP booster pump + HST booster heater.

Supreme temperature control solutions for the most demanding applications with powerful pressure/suction pump systems



### Heating Circulators with Open Bath with high quality stainless steel bath tank

- Internal and external temperature applications to 150°C
- EH-5 (to 150°C) as well as ED-5 and MB-5 (to +100°C) included a lift up bath cover. The units have a built in cooling coil.
- Large bath opening on the models with a filling volume of 13, 19, 27, 33 or 39 litres.

### Open Heating Bath circulators - the 'economy' series

Julabo	Working temp Range °C	Temperature stability °C	Heat capacity kW2	Pump Capacity Flow rate /min	Pressure bar	Cooling coil	Bath opening/ bath depth w x l/d cm	Bath cover	Filling volume Litres	Dimensions w x l x h cm	Weight kg
12260/01	20 to 100	±0.03	2/1	15	0.35	Option	18 x 30/15	Option	13	39 x 33 x 37	8.0
12260/02	20 to 100	±0.03	2/1	15	0.35	Option	36 x 30/15	Option	19	57 x 33 x 37	11.0
12260/03	20 to 100	±0.03	2/1	15	0.35	Option	36 x 30/20	Option	27	57 x 37 x 42	13.0
12260/04	20 to 100	±0.03	2/1	15	0.35	Option	67 x 30/15	Option	33	91 x 33 x 38	20.0

### Open Heating Bath circulators - the 'Top Tech' series

12260/05	20 to 100	±0.02	2/1	10	0.12	Option	18 x 30/15	Option	13	39 x 33 x 37	8
12260/06	20 to 100	±0.02	2/1	10	0.12	Option	18 x 30/20	Option	17	39 x 33 x 42	10
12260/07	20 to 100	±0.02	2/1	10	0.12	Option	36 x 30/15	Option	19	57 x 33 x 37	11

### Heating circulators with Open Bath - the 'Economy' Series

12260/08	20 to 100	±0.03	2	15	0.35	Integr.	15 x 15/15	Integr.	4.5	17 x 33 x 36	7.0
12260/09	20 to 150	±0.03	2/1	15	0.35	Integr.	15 x 15/15	Integr.	4.5	17 x 33 x 36	7.0
12260/10	20 to 150	±0.03	2/1	15	0.35	Option	18 x 30/15	Option	13	39 x 33 x 37	8.0
12260/11	20 to 150	±0.03	2/1	15	0.35	Option	36 x 30/15	Option	19	57 x 33 x 37	11.0
12260/12	20 to 150	±0.03	2/1	15	0.35	Option	36 x 30/20	Option	27	57 x 37 x 42	13.0
12260/13	20 to 150	±0.03	2/1	15	0.35	Option	67 x 30/15	Option	33	91 x 33 x 38	20.0
12260/14	20 to 150	±0.03	2/1	15	0.35	Option	36 x 30/30	Option	39	54 x 34 x 52	19.0

### Heating circulators with Open Bath - the 'Top Tech' Series

12260/15	20 to 100	±0.02	2/1	10	0.12	Integr.	15 x 15/15	Integr.	4.5	17 x 33 x 36	7.0
----------	-----------	-------	-----	----	------	---------	------------	---------	-----	--------------	-----

Product no	Working temp. range °C	Temp stab. °C	Heat cap. kW <sup>1</sup>	Pump capacity			Bath opening/ bath depth w x l/d cm	Fill. vol. litres	Dimensions w x l x h cm	Weight kg
				Flow rate l/min.	Press bar	Suction bar				
12230/10	20 to 250	±0.01	2/1	22-26	0.4-0.7	0.2-0.4	13 x 15/15	4.5	21 x 42 x 40	11
12230/11	20 to 300	±0.01	3/-	22-26	0.4-0.7	0.2-0.4	13 x 15/20	6	21 x 43 x 44	13.5
12230/12	20 to 300	±0.01	3/-	22-26	0.4-0.7	0.2-0.4	22 x 15/20	12	30 x 43 x 47	14
12230/13	20 to 300	±0.01	3/-	22-26	0.4-0.7	0.2-0.4	22 x 30/20	26	36 x 61 x 47	27
12230/14	20 to 250	±0.01	2/1	22-26	0.4-0.7	0.2-0.4	13 x 15/15	4.5	21 x 42 x 40	11
12230/15	20 to 250	±0.01	3/--	22-26	0.4-0.7	0.2-0.4	13 x 15/20	6	21 x 43 x 44	13.5
12230/16	20 to 300	±0.01	3/-	22-26	0.4-0.7	0.2-0.4	22 x 15/20	12	30 x 43 x 47	14
12230/17	20 to 300	±0.01	3/-	22-26	0.4-0.7	0.2-0.4	22 x 30/20	26	36 x 61 x 47	27